



(stand optional)




(cabinet optional)

EBA 4315(table top model)

EBA 4350(table top model)

430	430
40	40
35	35
435	435
electromechanical	electromechanical
"fast flick" action clamp	automatic clamp
manual	manual
hand crank	hand crank
digital display (mm/inches)	digital display (mm/inches)
• (electronically controlled)	• (electronically controlled)
electronic	electronic
•	•
•	•
•	•
•	•
stand or cabinet	stand or cabinet
355/1085 ¹ /1080 ² x 640 x 870	355/1085 ¹ /1080 ² x 640 x 870
230 V / 50 Hz / 0.45 kW	230 V / 50 Hz / 0.45 kW
81 / 91 ¹ / 113 ²	86 / 96 ¹ / 118 ²




Cutting stick change

Turning or exchanging the cutting stick can easily be managed from the outside of the guillotine without using any tools.



Digital measurement readout

The digital measurement readout allows exact positioning of the backgauge. The indication accuracy of the digital display is 1/10 mm (models 4315 and 4350).



Optical cutting line

The optical cutting line indicator with especially bright and durable LEDs guarantees easy alignment of cutting marks for precise cuts (models 4315 and 4350).



EASY-CU³ activating bars

The innovative cutting system with convenient two-hand operation via patented blade activating bars (models 4315 and 4350).

¹with stand ²with cabinet ³other voltages available

Electro-mechanical guillotines



EBA 4815

EBA 4850

Cutting length, mm	475	475
Cutting height, mm	80	80
Narrow cut, mm	30	30
Table depth, mm	458	458
Blade drive	electromechanical	electromechanical
Clamping system	spindle clamp	automatic clamp
Backgauge	manual	manual
Manual backgauge setting	hand crank	hand crank
Measurement indication	digital display (mm/inches) on front table	digital display (mm/inches) on front table
Electronic control for backgauge	-	-
Program mode	-	-
Blade made of German high quality steel	•	•
Optical cutting line indicator with bright LEDs	•	•
Electronically controlled safety cover on front table	•	•
Practical stand and storage shelf (standard equipment)	•	•
EASY-CUT patented blade activating bars (two-hand operation)	•	•
Practical hook-in tool holder on back table	•	•
Optional accessories (at an extra cost)	set of side tables	set of side tables
Dimensions, mm (H x W x D)	1410 x 762/1349 ³ x 1053	1296 x 762/1349 ³ x 1053
Power supply ⁶	230 V / 50 Hz / 1.1 kW	230 V / 50 Hz / 1.42 kW
Weight, kg	212 / 221 ³	225 / 234 ³




Practical tool holder

The practical hook-in tool holder is placed on the back table and keeps all necessary tools for blade change and service jobs within reach.



EASY-CUT activating bars

The innovative cutting system with convenient two-hand operation via patented blade activating bars.



Optical cutting line

The optical cutting line indicator with especially bright and durable LEDs guarantees easy alignment of cutting marks for precise cuts.



Digital measurement readout

The digital measurement readout allows an exact positioning of the backgauge, which is set by a hand crank.



EBA 4855

EBA 5255


EBA 6655

475	520	650
80	80	80
35	35	25
450	520	610
electromechanical	electromechanical	electromechanical
automatic clamp	automatic clamp	automatic clamp
electric	electric	electric
electronic hand wheel	electronic hand wheel	electronic hand wheel
digital display (mm/inches)	digital display (mm/inches)	digital display (mm/inches)
touch pad	touch pad	touch pad
99 programs, 99 steps	99 programs, 99 steps	99 programs, 99 steps
•	•	•
•	•	•
•	•	•
•	•	•
•	•	•
•	•	•
set of side tables	set of side tables	set of side tables
1296 x 762/1349 ³ x 992	1293 x 860/1436 ³ x 1120	1293 x 992/1565 ³ x 1220
230 V / 50 Hz / 1.42 kW	230 V / 50 Hz / 1.42 kW	230 V / 50 Hz / 1.42 kW
228 / 237 ³	252 / 261 ³	302 / 311 ³



Transparent safety guard

The electronically secured front safety guard swings out of the way easily and allows safe and convenient cutting.



Easy-to-use touch pad


Extremely convenient: Electronic, programmable control module for the power backgauge with multi-lingual touch pad.



Electronic hand wheel

Ideal for manual backgauge positioning, the electronic hand wheel has infinitely variable speed control (from very slow to very fast).

³with side tables ⁵other voltages available



Optional side tables

A set of side tables provides additional storage space and is available for all guillotines starting with model 4815 at an extra cost.

NEOSYS VIETLOI COMPANY LIMITED

Showroom: No.26B, Street 10, Thao Dien Ward, Dist.2, HCMC, Vietnam
 HN Branch: 3rd Floor, No.6, Lane 2, Quan Ngua St., Ba Dinh Dist., Hanoi, Vietnam
 Tel: (+8428) 22532772/ 25532773 - Fax: (+8428) 22532771
 Website: www.neosys-vietloi.com.vn
 Email: info@neosys-vietloi.com.vn
 Hotline: 0902 886 117