

### 2. Touch Screen Display

The 7" color touch screen enables navigation easily to create a new job or access existing jobs within seconds

### 1. Automated Stacker

The high-capacity vertical stacker holds up to 500 finished envelopes

### 3. CIS Scanner

Internal Contact Image Sensor (CIS) scanner can read OMR, OCR, 1D and 2D codes printed horizontally or vertically on the document



### 4. Document Feeders

Process multiple page sets at high processing speeds using three standard feeders holding up to 975 documents (3 x 325). While in cascade mode, feeder sensors ensure continuous operation



#### A State-of-the-Art Graphical User Interface

Designed for all users, the intuitive, full color, high-resolution 7" touch screen provides a wizard-based, user-friendly interface, making it easy for anyone to select and run their folding and inserting jobs.

And, see how easy it is to create a new job. Simply load your documents and envelopes and press the start button. The DS-75i will automatically measure the length of all loaded documents, as well as the envelope, in order to adjust all settings and process the appropriate mail items.




#### Smart Solutions to Maximize Flexibility

The exclusive FlexFeed® tray enables you to process many different document sizes. In combination with the unique semi-automatic envelope separation mechanism, this provides full flexibility for feeding a wide variety of document types.

#### Optimize Productivity with the MaxiFeeder Tray

Choose to load the MaxiFeeder with up to 325 BREs or load up to 1,200 sheets to maximize your productivity.

Specifications	
Processing speed	Up to 3,800/hour
Color touch screen	Standard
Automatic settings	Standard
Job memory	50
Feeders	Up to 3
Hand feeding	Standard
Multi-sheet feeding	Standard
Cascade from feeders	Standard
Document feeder capacity	325 sheets (20 lb.)
High capacity feeder capacity	725 sheets (20 lb.)
Envelope feeder capacity	325
Folding capacity (one set, single fold)	Standard (Up to 10 sheets 20 lb.)
Automatic double detection	Standard
Accumulate before folding	Standard
High capacity vertical stacker	Up to 500 envelopes
Tip-to-tip sealing	Standard
LAN embedded	Standard
Wireless embedded	Standard
Noise level	66 Db
Fold types	Letter, z-fold, single, double, parallel, no fold 
Document height	3.5" - 14"
Document width	5.1" - 9.1"
Envelope length	3.5" - 6.35"
Envelope width	6.3" - 9.7"
Maximum insert thickness	1 mm
Maximum set thickness	2.5 mm
Options	
MaxiFeeder capacity	1,200 sheets (20 lb.)/325 BRE
Side exit	Up to 400 envelopes
Mailing system interface	Available
Barcode Reader (BCR) for 1D and 2D barcodes	Available
Optical Mark Recognition (OMR)	Available
Optical Character Recognition (OCR)	Available
Output Management Software (OMS)	Available
Remote Assistance	Available
Remote Diagnostics	Available
System Dimensions	
DS-75i (3 feeders with catch tray)	50" x 20" x 29"
Weight	175 lbs.

## We've Got You Covered

Quadient maintains a network of offices across the country to provide local customer support and trained technicians who are ready to assist you. You can be confident that when you need knowledgeable support or expert service, the point-of-contact will be a Quadient office in your area consisting of a team of local professionals.

## About Quadient

Quadient is the driving force behind the world's most meaningful customer experiences. By focusing on four key solution areas including Customer Experience Management, Business Process Automation, Mail-related Solutions, and Parcel Locker Solutions, Quadient helps simplify the connection between people and what matters. Quadient supports hundreds of thousands of customers worldwide in their quest to create relevant, personalized connections and achieve customer experience excellence. Quadient is listed in compartment B of Euronext Paris (QDT) and belongs to the SBF 120 index.

For more information about Quadient, visit [quadient.com](http://quadient.com).

## NEOSYS VIETLOI COMPANY LIMITED

Showroom: No.26B, Street 10, Thao Dien Ward, Dist.2, HCMC, Vietnam  
 HN Branch: 3rd Floor, No.6, Lane 2, Quan Ngua St., Ba Dinh Dist., Hanoi, Vietnam  
 Tel: (+8428) 22532772/ 25532773 - Fax: (+8428) 22532771  
 Website: [www.neosys-vietloi.com.vn](http://www.neosys-vietloi.com.vn)  
 Email: [info@neosys-vietloi.com.vn](mailto:info@neosys-vietloi.com.vn)  
**Hotline: 0902 886 117**

